

Safety Agreement

As an installation subcontractor for Coast Sign Incorporated, you are required to maintain an ongoing safety program. This agreement is for the minimum safety requirements as required by Coast Sign Inc. You are completely responsible for safety on site.

Prior to beginning any Coast Sign project, all contractors will hold a safety meeting between management and the workmen assigned. The agenda will address all OSHA requirements for workplace safety. Sign Installers & Contractors should especially give emphasis to the following requirements:(The scope of your work will vary, items pertain where applicable.)

1. Any hydraulic equipment shall be checked daily for hydraulic leaks, defective valves and bent cylinder tubes. Any items noted shall be repaired prior to operation. All outriggers will be inspected for proper function and will be deployed prior to beginning any lift.
2. All lifting cables, slings, chokers and webs shall be inspected for broken strands, kinks, corrosion and loose bindings prior to use. Sheaves, blocks and pulleys will be inspected for worn shafts, hooks and cracked or chipped sheave grooves. Any item displaying one of these characteristics will be discarded and replaced. All hooks will require a functional safety latch.
3. All tools, cords and ladders must be in good repair. Broken housing, frayed cords, broken insulation or unsafe ladders are not allowed on the jobsite at any time.
4. Safety harnesses and lines will be inspected for defects prior to use and replaced if found defective. These devices must be worn and properly rigged prior to beginning any personnel lifts or work above six (6) feet.
5. All staging will be set up, tied off and inspected by a qualified staging rigger prior to beginning any lifts.
6. Proper eye protection will be worn as necessary at all times. The type of protection is dictated by the work being performed (i.e. Welding glasses or hoods when welding or clear shields when grinding etc.)
7. Public access areas underneath overhead work areas will be cordoned off, safety netting will be installed overhead and site access limited to those necessary for execution of the work. Hard hats are required whenever the local ordinances warrant or whenever there is work being performed overhead.
8. Safety steel toe shoes are required on any jobsite. Open toe shoes, sandals or canvas type shoes are not allowed while on the jobsite at any time.
9. Proper attire shall be worn at all times. No loose, torn or oversized clothing is allowed at the jobsite. No short pants, sleeveless shirts or tank tops are allowed on the jobsite.
10. Any personnel or visitors to the site will be given thorough safety instructions prior to admission to the site. OSHA guidelines will be your primary requirement. Additionally, there may be safety requirements instituted by our mutual customer.

If at any time the requirements of Coast Sign Incorporated, the customer or OSHA are not consistent, the most stringent requirement will prevail. Safety for your workmen, as well as the general public, is the most important aspect of the work.

All requirements must be adhered to without exception.

Filled in data below includes acceptance of the Safety Agreement, and terms and conditions herein.

Company Name:

Name:

Title:

Date: